

# Tartan Inlet Breechings

**2 Ways Breeching Inlet**                      **MT-401023**

**4 Ways Breeching Inlet**                      **MT-401063**

**Manufactured and approved to BS5041-3**




## Common features

- Construction and performance in accordance with BS5041 part 3
- Materials - Ductile Cast Iron Body with Gunmetal fittings
- Inlets complete with spring loaded non-return valves and plastic blanking caps
- Fitted with BS5154 25 mm (1") brass drain valve complete with cap & chain
- Working Pressure 20 bar, Test Pressure 30bar. Non-return valve test pressure 1.7 bar
- Finish - Red RAL3000




Breeching Inlet	2 - Way	4 - Way
Part No	MT- 401023	MT- 401063
Dimensions (mm) W x D x H	300 x 225 x 100	330 x 215 x 150
D Inlet connections	2 x 65mm Inst Male BS336	4 x 65mm Inst Male BS336
Outlet connection	100 mm (4") Flange drilled NP16 BS4504	150 mm (6") Flange drilled NP16 BS4504
Weight (kg)	16.0	32.0

2 Way Breeching



4 Way Breeching



License No. KM 647384

## INTERNATIONAL SALES

**Angus Fire Ltd**  
 Angus House, Haddenham Business Park,  
 Pegasus Way, Haddenham, Aylesbury, HP17 8LB, UK  
 Tel: +44 (0)1844 293600 • Fax: +44 (0)1844 293664

## UK SALES

**Angus Fire Ltd**  
 Station Road, Bentham, Lancaster, LA2 7NA, UK  
 Tel: +44 (0)1524 264000 • Fax: +44 (0)1524 264180

Angus Fire operates a continuous programme of product development. The right is therefore reserved to modify any specification without prior notice and Angus Fire should be contacted to ensure that the current issues of all technical data sheets are used.

© Angus Fire  
 6846/1 02/17