



JetFoam ICAO-C

Fluorine Free (FF)
Foam Concentrate

- A superior quality synthetic Fluorine Free Foam concentrate
- Low viscosity allows for induction and airport crash vehicle compatibility
- Provides a vapour-sealing aqueous film over the fuel surface to provide rapid control and extinguishment
- Use in high risk situations where hydrocarbons are stored, processed or transported
- Use at 3% or 6%. It is readily proportioned using conventional foam proportioning equipment
- Compatible with air-aspirating discharge devices
- Suitable for use with potable and fresh water
- Suitable for use with foam compatible dry powder extinguishing agents
- 100% biodegradable



JetFoam ICAO-C is a superior quality synthetic fluorine free (FF) foams concentrate, designed for extinguishing and securing flammable aviation fuel spills and fires (Jet A and Jet A1).

JetFoam ICAO-C is a patented combination of surfactants and other ingredients and produces a vapour sealing blanket of foam that rapidly spreads over the surface of the fuel to provide rapid control and extinguishment.

- Unique patented formulation only available from Angus Fire.
- The world's first truly Newtonian fluorine free foam (it behaves like water due to not containing any polymers or gelling agents).
- Specifically designed for the aviation sector's focused risks.

Applications

JetFoam ICAO-C is used in high risk situations where hydrocarbon fuels such as Jet-A, Jet-A1 and aviation kerosene are processed, stored or transported.

It is designed to be used on Aviation Rescue Fire Fighting Vehicles (ARFFV), Rapid Intervention Vehicles (RIV) and airport crash trucks where fast extinguishment is essential for saving life. JetFoam ICAO-C provides a vapour suppressing foam blanket on Jet-A and Jet-A1 spills.

Approvals and listings

JetFoam ICAO-C meets and exceeds the requirements of ICAO 2013 Level C and is certified to this performance level.

Equipment

JetFoam ICAO-C is readily proportioned using conventional foam proportioning equipment.

JetFoam ICAO-C 3% is intended for use at 3% (3 parts concentrate to 97 parts water) and JetFoam ICAO-C 6% is intended for use at 6% (6 parts concentrate to 94 parts water).
Please refer to the table overleaf.

JetFoam ICAO-C can be used with air aspirating devices. Where a fire or shallow spill is involved with fire, Angus Fire always recommends the use of aspirated foam where a stable foam blanket is essential.

Compatibility

JetFoam ICAO-C is suitable for use in combination with:

- Potable and fresh water.
- Expanded protein-based or synthetic foams for application to a fire in sequence or simultaneously.
- Dry powder extinguishing agents either separately or as twin agent systems.

JetFoam ICAO-C

Fluorine Free (FF) Foam Concentrate

Environment

JetFoam ICAO-C contains no fluorosurfactants, fluoropolymers, organohalogens, PFAS, PFOA and no PFOS in accordance with EU Directive 2006/122/EC and amended Council Directive 76/769/EEC.

JetFoam ICAO-C is 100% biodegradable.

Please refer to the product's Safety Data Sheet (SDS) and website for more information regarding the use, discharge and disposal of all firefighting foam products.

Storage

JetFoam ICAO-C is exceptionally stable in long-term storage. A shelf-life of at least ten years can be expected if it is stored properly.

Disposal

For fire water runoff and accidental spillage please refer to Angus Fire's Foam Disposal Guide and MSDS for more information

Product Quality

JetFoam ICAO-C production is closely controlled, Angus Fire operates a quality management system which complies with the requirements of BE EN ISO 9001.

Typical Physico-Chemical Properties	3%	6%
Appearance	Clear mobile liquid	Clear mobile liquid
Specific gravity @ 20°C	0.99 – 1.01	0.99 – 1.01
pH	8-9	8-9
Viscosity @ 20°C	60 - 100mm ² s	20 - 50mm ² s
Maximum continuous storage	50°C	50°C
Maximum intermittent storage	60°C	60°C
Effect of freeze/thaw	None	None
Lowest use temperature	0°C	0°C
Sediment as shipped	≤ 0.1%	≤ 0.1%
Sediment after ageing	≤ 0.1%	≤ 0.1%

Typical Foam Properties:	3%	6%
Induction rate	3%	6%
Expansion ratio	≥ 7:1	≥ 7:1
25% drainage time	≥ 3 minutes	≥ 3 minutes

Packing Specification					
	Plastic Square	Plastic Square	Plastic Cylindrical	Plastic Cylindrical	Ecobulk MX
Capacity	25 litres	5 US gallons	200 litres	55 US gallons	1000 litres
Filled weight (kg)	26	20	209	218	1070
Dimensions (mm)	448 x 286 x 286	402 x 293 x 240	580 D x 922 H	580 D x 922 H	1200 L x 1000 W x 1160 H
Part Number 3%	FN0511G0P	FN0511T0P	FN0511J0P	FN0511W0P	FN0511L8
Part Number 6%	FN0512G0P	FN0512T0P	FN0512J0P	FN0512W0P	FN0512L8



EMERGENCY FOAM SERVICE Call +44 (0) 15242 61166 – 24 hours a day, every day



GENERAL SALES Angus Fire Ltd

Station Road, Bentham, Lancaster, LA2 7NA, UK
Tel: +44 (0)1524 264000 • Fax: +44 (0)1524 261580

Angus Fire operates a continuous programme of product development. The right is therefore reserved to modify any specification without prior notice and Angus Fire should be contacted to ensure that the current issues of all technical data sheets are used.

© Angus Fire 6905/1 03/24